

Chemwatch Material Safety Data Sheets

The Evic Group™ - 20 Lancaster Street Ingleburn, NSW 2565 Australia

For further enquiries (freecall) 1800 761 761

For further Product Information visit www.evic.com.au



EVIC 853-859A SPRAYTHANE TEXTURED POLYURETHANE PART A

Chemwatch Material Safety Data Sheet

Issue Date: 26-Sep-2008

NA317TC

CHEMWATCH 5093-30

Version No:4

CD 2008/4 Page 1 of 19

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

EVIC 853-859A SPRAYTHANE TEXTURED POLYURETHANE PART A

PROPER SHIPPING NAME

PAINT RELATED MATERIAL

PRODUCT USE

» The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing.

Before starting consider control of exposure by mechanical ventilation.

Base or Part A of a 2 pack.

urethane coating system.

Requires that the two parts be mixed by hand or mixer before use, in accordance with manufacturers directions. Mix only as much as is required. Do not return the mixed material to the original containers.

Application is usually by spray atomisation.

For kitchen doors, vanities and similar surfaces requiring a hard wearing textured surface

SUPPLIER

Company: Evic Pty Ltd

Address:

20 Lancaster Street

Ingleburn

NSW, 2565

AUS

Telephone: +61 2 9829 2288

Telephone: 1800 251 633

Fax: +61 2 9829 1612

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

CHEMWATCH HAZARD RATINGS

continued...

EVIC 853-859A SPRAYTHANE TEXTURED POLYURETHANE PART A

Chemwatch Material Safety Data Sheet

Issue Date: 26-Sep-2008


NA317TC

CHEMWATCH 5093-30

Version No:4

CD 2008/4 Page 2 of 19

Section 2 - HAZARDS IDENTIFICATION



POISONS SCHEDULE

S5

RISK

- » Highly flammable.
- » May form explosive peroxides.
- » Harmful by inhalation and in contact with skin.
- » Limited evidence of a carcinogenic effect.
- » May impair fertility.
- » May cause harm to the unborn child.
- » HARMFUL- May cause lung damage if swallowed.
- » Vapours may cause drowsiness and dizziness.

SAFETY

- » Keep locked up.
- » Keep away from sources of ignition. No smoking.
- » Do not breathe gas/fumes/vapour/spray.
- » In case of insufficient ventilation wear suitable respiratory equipment.
- » Use only in well ventilated areas.
- » Keep container in a well ventilated place.
- » Avoid exposure - obtain special instructions before use.
- » To clean the floor and all objects contaminated by this material use water and detergent.
- » Keep container tightly closed.
- » This material and its container must be disposed of in a safe way.
- » Keep away from food drink and animal feeding stuffs.
- » In case of contact with eyes rinse with plenty of water and contact Doctor or Poisons Information Centre.
- » This material and its container must be disposed of as hazardous waste.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
polyester resin		10-30
pigment		10-30
2- ethoxyethyl acetate	111-15-9	5-20
aromatic solvent		1-10
toluene	108-88-3	1-10
alkyl ester		1-10
alkyl ketone		1-10
ingredients determined not to be hazardous		1-10

Section 4 - FIRST AID MEASURES

SWALLOWED

- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.

continued...

EVIC 853-859A SPRAYTHANE TEXTURED POLYURETHANE PART A

Chemwatch Material Safety Data Sheet

Issue Date: 26-Sep-2008

NA317TC

CHEMWATCH 5093-30

Version No:4

CD 2008/4 Page 3 of 19

Section 4 - FIRST AID MEASURES

- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Seek medical advice.
- Avoid giving milk or oils.
- Avoid giving alcohol.
- If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.

EYE

» If this product comes in contact with the eyes:

- Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- If pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

» If skin contact occurs:

- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor.

NOTES TO PHYSICIAN

» Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours.

For acute or short term repeated exposures to petroleum distillates or related hydrocarbons:

- Primary threat to life, from pure petroleum distillate ingestion and/or inhalation, is respiratory failure.
- Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO₂ 50 mm Hg) should be intubated.
- Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
- A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.
- Epinephrine (adrenalin) is not recommended for treatment of bronchospasm because of potential myocardial sensitisation to catecholamines. Inhaled cardioselective bronchodilators (e.g. Alupent, Salbutamol) are the preferred agents, with aminophylline a second choice.
- Lavage is indicated in patients who require decontamination; ensure use of cuffed endotracheal tube in adult patients. [Ellenhorn and Barceloux: Medical Toxicology].

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Foam.
- Dry chemical powder.

continued...

EVIC 853-859A SPRAYTHANE TEXTURED POLYURETHANE PART A

Chemwatch Material Safety Data Sheet

Issue Date: 26-Sep-2008

NA317TC

CHEMWATCH 5093-30

Version No:4

CD 2008/4 Page 4 of 19

Section 5 - FIRE FIGHTING MEASURES

- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog - Large fires only.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- Consider evacuation (or protect in place).
- Fight fire from a safe distance, with adequate cover.
- If safe, switch off electrical equipment until vapour fire hazard removed.
- Use water delivered as a fine spray to control the fire and cool adjacent area.
- Avoid spraying water onto liquid pools.
- Do not approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.

FIRE/EXPLOSION HAZARD

- Liquid and vapour are highly flammable.
- Severe fire hazard when exposed to heat, flame and/or oxidisers.
- Vapour may travel a considerable distance to source of ignition.
- Heating may cause expansion or decomposition leading to violent rupture of containers.
- On combustion, may emit toxic fumes of carbon monoxide (CO).

Combustion products include: carbon dioxide (CO₂), other pyrolysis products typical of burning organic material.
Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions.

FIRE INCOMPATIBILITY

- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

HAZCHEM: None

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb small quantities with vermiculite or other absorbent material.
- Wipe up.
- Collect residues in a flammable waste container.

MAJOR SPILLS

» Chemical Class: aromatic hydrocarbons

For release onto land: recommended sorbents listed in order of priority.

SORBENT TYPE	RANK	APPLICATION	COLLECTION	LIMITATIONS
LAND SPILL - SMALL				
Feathers - pillow	1	throw	pitchfork	DGC, RT
cross- linked	2	shovel	shovel	R, W, SS

continued...

EVIC 853-859A SPRAYTHANE TEXTURED POLYURETHANE PART A

Chemwatch Material Safety Data Sheet

Issue Date: 26-Sep-2008

NA317TC

CHEMWATCH 5093-30

Version No:4

CD 2008/4 Page 5 of 19

Section 6 - ACCIDENTAL RELEASE MEASURES

polymer - particulate cross- linked	2	throw	pitchfork	R, DGC, RT
polymer- pillow sorbent clay - particulate	3	shovel	shovel	R, I, P,
treated clay/ treated natural organic - particulate	3	shovel	shovel	R, I
wood fibre - pillow	4	throw	pitchfork	R, P, DGC, RT

LAND SPILL - MEDIUM

cross- linked polymer - particulate	1	blower	skiloader	R, W, SS
treated clay/ treated natural organic - particulate	2	blower	skiloader	R, I
sorbent clay - particulate	3	blower	skiloader	R, I, P
polypropylene - particulate	3	blower	skiloader	W, SS, DGC
feathers - pillow	3	throw	skiloader	DGC, RT
expanded mineral - particulate	4	blower	skiloader	R, I, W, P, DGC

Legend

DGC: Not effective where ground cover is dense

R; Not reusable

I: Not incinerable

P: Effectiveness reduced when rainy

RT: Not effective where terrain is rugged

SS: Not for use within environmentally sensitive sites

W: Effectiveness reduced when windy

Reference: Sorbents for Liquid Hazardous Substance Cleanup and Control;

R.W Melvold et al: Pollution Technology Review No. 150: Noyes Data Corporation 1988.

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- Consider evacuation (or protect in place).
- No smoking, naked lights or ignition sources.
- Increase ventilation.
- Stop leak if safe to do so.
- Water spray or fog may be used to disperse /absorb vapour.
- Contain spill with sand, earth or vermiculite.
- Use only spark-free shovels and explosion proof equipment.
- Collect recoverable product into labelled containers for recycling.
- Absorb remaining product with sand, earth or vermiculite.
- Collect solid residues and seal in labelled drums for disposal.
- Wash area and prevent runoff into drains.
- If contamination of drains or waterways occurs, advise emergency services.

continued...

EVIC 853-859A SPRAYTHANE TEXTURED POLYURETHANE PART A

Chemwatch Material Safety Data Sheet

Issue Date: 26-Sep-2008

NA317TC


CHEMWATCH 5093-30

Version No:4

CD 2008/4 Page 6 of 19

Section 6 - ACCIDENTAL RELEASE MEASURES

PROTECTIVE ACTIONS FOR SPILL



From IERG (Canada/Australia)

Isolation Distance	25 metres
Downwind Protection Distance	300 metres
IERG Number	14

FOOTNOTES

- 1 PROTECTIVE ACTION ZONE is defined as the area in which people are at risk of harmful exposure. This zone assumes that random changes in wind direction confines the vapour plume to an area within 30 degrees on either side of the predominant wind direction, resulting in a crosswind protective action distance equal to the downwind protective action distance.
- 2 PROTECTIVE ACTIONS should be initiated to the extent possible, beginning with those closest to the spill and working away from the site in the downwind direction. Within the protective action zone a level of vapour concentration may exist resulting in nearly all unprotected persons becoming incapacitated and unable to take protective action and/or incurring serious or irreversible health effects.
- 3 INITIAL ISOLATION ZONE is determined as an area, including upwind of the incident, within which a high probability of localised wind reversal may expose nearly all persons without appropriate protection to life-threatening concentrations of the material.
- 4 SMALL SPILLS involve a leaking package of 200 litres (55 US gallons) or less, such as a drum (jerrican or box with inner containers). Larger packages leaking less than 200 litres and compressed gas leaking from a small cylinder are also considered "small spills".
LARGE SPILLS involve many small leaking packages or a leaking package of greater than 200 litres, such as a cargo tank, portable tank or a "one-tonne" compressed gas cylinder.
- 5 Guide 128 is taken from the US DOT emergency response guide book.
- 6 IERG information is derived from CANUTEC - Transport Canada.

EMERGENCY RESPONSE PLANNING GUIDELINES (ERPG)

The maximum airborne concentration below which it is believed that nearly all individuals could be exposed for up to one hour WITHOUT experiencing or developing

life-threatening health effects is:

toluene 1000ppm

irreversible or other serious effects or symptoms which could impair an individual's ability to take protective action is:

toluene 300ppm

other than mild, transient adverse effects without perceiving a clearly defined odour is:

toluene 50ppm

American Industrial Hygiene Association (AIHA)

Ingredients considered according to the following cutoffs

Very Toxic (T+)	>= 0.1%	Toxic (T)	>= 3.0%
-----------------	---------	-----------	---------

continued...

EVIC 853-859A SPRAYTHANE TEXTURED POLYURETHANE PART A

Chemwatch Material Safety Data Sheet

Issue Date: 26-Sep-2008

NA317TC

CHEMWATCH 5093-30

Version No:4

CD 2008/4 Page 7 of 19

Section 6 - ACCIDENTAL RELEASE MEASURES

R50	$\geq 0.25\%$	Corrosive (C)	$\geq 5.0\%$
R51	$\geq 2.5\%$		
else	$\geq 10\%$		

where percentage is percentage of ingredient found in the mixture

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Containers, even those that have been emptied, may contain explosive vapours.
- Do NOT cut, drill, grind, weld or perform similar operations on or near containers.

Contains low boiling substance:

Storage in sealed containers may result in pressure buildup causing violent rupture of containers not rated appropriately.

- Check for bulging containers.
 - Vent periodically
 - Always release caps or seals slowly to ensure slow dissipation of vapours.
 - DO NOT allow clothing wet with material to stay in contact with skin.
- The tendency of many ethers to form explosive peroxides is well documented. Ethers lacking non-methyl hydrogen atoms adjacent to the ether link are thought to be relatively safe
- DO NOT concentrate by evaporation, or evaporate extracts to dryness, as residues may contain explosive peroxides with DETONATION potential.
 - Any static discharge is also a source of hazard.
 - Before any distillation process remove trace peroxides by shaking with excess 5% aqueous ferrous sulfate solution or by percolation through a column of activated alumina.
 - Distillation results in uninhibited ether distillate with considerably increased hazard because of risk of peroxide formation on storage.
 - Add inhibitor to any distillate as required.
 - When solvents have been freed from peroxides by percolation through columns of activated alumina, the absorbed peroxides must promptly be desorbed by treatment with polar solvents such as methanol or water, which should then be disposed of safely.
 - Electrostatic discharge may be generated during pumping - this may result in fire.
 - Ensure electrical continuity by bonding and grounding (earthing) all equipment.
 - Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (≤ 1 m/sec until fill pipe submerged to twice its diameter, then ≤ 7 m/sec).
 - Avoid splash filling.
 - Do NOT use compressed air for filling discharging or handling operations.
 - Avoid all personal contact, including inhalation.
 - Wear protective clothing when risk of exposure occurs.
 - Use in a well-ventilated area.
 - Prevent concentration in hollows and sumps.
 - DO NOT enter confined spaces until atmosphere has been checked.
 - Avoid smoking, naked lights, heat or ignition sources.
 - When handling, DO NOT eat, drink or smoke.
 - Vapour may ignite on pumping or pouring due to static electricity.
 - DO NOT use plastic buckets.
 - Earth and secure metal containers when dispensing or pouring product.
 - Use spark-free tools when handling.
 - Avoid contact with incompatible materials.
 - Keep containers securely sealed.
 - Avoid physical damage to containers.
 - Always wash hands with soap and water after handling.
 - Work clothes should be laundered separately.
 - Use good occupational work practice.
 - Observe manufacturer's storing and handling recommendations.

continued...

EVIC 853-859A SPRAYTHANE TEXTURED POLYURETHANE PART A

Chemwatch Material Safety Data Sheet

Issue Date: 26-Sep-2008

NA317TC

CHEMWATCH 5093-30

Version No:4

CD 2008/4 Page 8 of 19

Section 7 - HANDLING AND STORAGE

- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.

SUITABLE CONTAINER

- Packing as supplied by manufacturer.
- Plastic containers may only be used if approved for flammable liquid.
- Check that containers are clearly labelled and free from leaks.
- For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.
- For materials with a viscosity of at least 2680 cSt. (23 deg. C)
- For manufactured product having a viscosity of at least 250 cSt. (23 deg. C)
- Manufactured product that requires stirring before use and having a viscosity of at least 20 cSt (25 deg. C)
- (i) : Removable head packaging;
- (ii) : Cans with friction closures and
- (iii) : low pressure tubes and cartridges may be used.
- Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact with inner and outer packages
- In addition, where inner packagings are glass and contain liquids of packing group I there must be sufficient inert absorbent to absorb any spillage, unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.

STORAGE INCOMPATIBILITY

- Glycol ethers may form peroxides under certain conditions.
- In the presence of strong bases or the salts of strong bases, at elevated temperatures, the potential exists for runaway reactions.
- Contact with aluminium should be avoided; release of hydrogen gas may result- will corrode scratched aluminium surfaces.
- Avoid reaction with oxidising agents.

STORAGE REQUIREMENTS

- Store in original containers in approved flame-proof area.
- No smoking, naked lights, heat or ignition sources.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- Keep containers securely sealed.
- Store away from incompatible materials in a cool, dry well ventilated area.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³
Australia Exposure Standards	2- ethoxyethyl acetate (2-Ethoxyethyl acetate)	5	27		
Australia Exposure Standards	toluene (Toluene)	50	191	150	574

EMERGENCY EXPOSURE LIMITS

Material	Revised IDLH Value (mg/m ³)	Revised IDLH Value (ppm)
2- ethoxyethyl acetate		500
toluene		500

continued...

EVIC 853-859A SPRAYTHANE TEXTURED POLYURETHANE PART A

Chemwatch Material Safety Data Sheet

Issue Date: 26-Sep-2008

NA317TC

CHEMWATCH 5093-30

Version No:4

CD 2008/4 Page 9 of 19

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

MATERIAL DATA

» Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations. Present day expectations require that nearly every individual should be protected against even minor sensory irritation and exposure standards are established using uncertainty factors or safety factors of 5 to 10 or more. On occasion animal no-observable-effect-levels (NOEL) are used to determine these limits where human results are unavailable. An additional approach, typically used by the TLV committee (USA) in determining respiratory standards for this group of chemicals, has been to assign ceiling values (TLV C) to rapidly acting irritants and to assign short-term exposure limits (TLV STELs) when the weight of evidence from irritation, bioaccumulation and other endpoints combine to warrant such a limit. In contrast the MAK Commission (Germany) uses a five-category system based on intensive odour, local irritation, and elimination half-life. However this system is being replaced to be consistent with the European Union (EU) Scientific Committee for Occupational Exposure Limits (SCOEL); this is more closely allied to that of the USA.

OSHA (USA) concluded that exposure to sensory irritants can:

- cause inflammation
- cause increased susceptibility to other irritants and infectious agents
- lead to permanent injury or dysfunction
- permit greater absorption of hazardous substances and
- acclimate the worker to the irritant warning properties of these substances thus increasing the risk of overexposure.

INGREDIENT DATA

2-ETHOXYETHYL ACETATE:

Odour Threshold Value: 0.06 ppm (detection), 0.13 ppm (recognition) This substance is readily hydrolysed in the body yielding ethylene glycol monoethyl ether which is a putative reproductive toxin. The TLV-TWA is thought to be protective against testicular effects.

TOLUENE:

» For toluene:

Odour Threshold Value: 0.16-6.7 (detection), 1.9-69 (recognition)

NOTE: Detector tubes measuring in excess of 5 ppm, are available.

High concentrations of toluene in the air produce depression of the central nervous system (CNS) in humans. Intentional toluene exposure (glue-sniffing) at maternally-intoxicating concentration has also produced birth defects. Foetotoxicity appears at levels associated with CNS narcosis and probably occurs only in those with chronic toluene-induced kidney failure. Exposure at or below the recommended TLV-TWA is thought to prevent transient headache and irritation, to provide a measure of safety for possible disturbances to human reproduction, the prevention of reductions in cognitive responses reported amongst humans inhaling greater than 40 ppm, and the significant risks of hepatotoxic, behavioural and nervous system effects (including impaired reaction time and incoordination). Although toluene/ethanol interactions are well recognised, the degree of protection afforded by the TLV-TWA among drinkers is not known.

Odour Safety Factor(OSF)

OSF=17 (TOLUENE).

PERSONAL PROTECTION

EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

continued...

EVIC 853-859A SPRAYTHANE TEXTURED POLYURETHANE PART A

Chemwatch Material Safety Data Sheet

Issue Date: 26-Sep-2008

NA317TC

CHEMWATCH 5093-30

Version No:4

CD 2008/4 Page 10 of 19

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

HANDS/FEET

- Wear chemical protective gloves, eg. PVC.
- Wear safety footwear or safety gumboots, eg. Rubber.

Suitability and durability of glove type is dependent on usage. Factors such as:

- frequency and duration of contact,
- chemical resistance of glove material,
- glove thickness and
- dexterity,

are important in the selection of gloves.

OTHER

- Overalls.
- PVC Apron.
- PVC protective suit may be required if exposure severe.
- Eyewash unit.
- Ensure there is ready access to a safety shower.
- Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity.

RESPIRATOR

» Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Breathing Zone Level ppm (volume)	Maximum Protection Factor	Half- face Respirator	Full- Face Respirator
1000	10	A- AUS	-
1000	50	-	A- AUS
5000	50	Airline *	-
5000	100	-	A- 2
10000	100	-	A- 3
	100+		Airline**

* - Continuous Flow

** - Continuous-flow or positive pressure demand.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

» For flammable liquids and flammable gases, local exhaust ventilation or a process enclosure ventilation system may be required. Ventilation equipment should be explosion-resistant.

Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25- 0.5 m/s (50- 100 f/min.)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5- 1 m/s (100- 200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1- 2.5 m/s (200- 500 f/min.)

continued...

EVIC 853-859A SPRAYTHANE TEXTURED POLYURETHANE PART A

Chemwatch Material Safety Data Sheet

Issue Date: 26-Sep-2008

NA317TC

CHEMWATCH 5093-30

Version No:4

CD 2008/4 Page 11 of 19

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Within each range the appropriate value depends on:

Lower end of the range

1: Room air currents minimal or favourable to capture

2: Contaminants of low toxicity or of nuisance value only.

3: Intermittent, low production.

4: Large hood or large air mass in motion

Upper end of the range

1: Disturbing room air currents

2: Contaminants of high toxicity

3: High production, heavy use

4: Small hood- local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

White highly flammable liquid with a strong solvent odour; does not mix with water

PHYSICAL PROPERTIES

Liquid.

Does not mix with water.

Sinks in water.

Molecular Weight: Not Available

Melting Range (°C): Not Available

Solubility in water (g/L): Immiscible

pH (1% solution): Not Applicable

Volatile Component (%vol): Not Available

Relative Vapour Density (air=1): >1

Lower Explosive Limit (%): Not Available

Autoignition Temp (°C): Not Available

State: Liquid

Boiling Range (°C): 78- 156

Specific Gravity (water= 1): 1.12- 1.15

pH (as supplied): Not Applicable

Vapour Pressure (kPa): Not Available

Evaporation Rate: Not Available

Flash Point (°C): 0

Upper Explosive Limit (%): Not Available

Decomposition Temp (°C): Not Available

Viscosity: Not Available

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

For incompatible materials - refer to Section 7 - Handling and Storage.

continued...

EVIC 853-859A SPRAYTHANE TEXTURED POLYURETHANE PART A

Chemwatch Material Safety Data Sheet

Issue Date: 26-Sep-2008

NA317TC

CHEMWATCH 5093-30

Version No:4

CD 2008/4 Page 12 of 19

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

» Swallowing of the liquid may cause aspiration of vomit into the lungs with the risk of haemorrhaging, pulmonary oedema, progressing to chemical pneumonitis; serious consequences may result.

Signs and symptoms of chemical (aspiration) pneumonitis may include coughing, gasping, choking, burning of the mouth, difficult breathing, and bluish coloured skin (cyanosis).

Accidental ingestion of the material may be damaging to the health of the individual.

EYE

» Limited evidence or practical experience suggests, that the material may cause moderate eye irritation in a substantial number of individuals and/or may produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals. Repeated or prolonged exposure may cause moderate inflammation (similar to windburn) characterised by a temporary redness of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.

SKIN

» Skin contact with the material may be harmful; systemic effects may result following absorption.

The material may produce moderate skin irritation; limited evidence or practical experience suggests, that the material either:

- produces moderate inflammation of the skin in a substantial number of individuals following direct contact and/or
- produces significant, but moderate, inflammation when applied to the healthy intact skin of animals (for up to four hours), such inflammation being present twenty-four hours or more after the end of the exposure period.

Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis.

Open cuts, abraded or irritated skin should not be exposed to this material.

Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

INHALED

» Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by narcosis, reduced alertness, loss of reflexes, lack of coordination and vertigo.

Limited evidence or practical experience suggests that the material may produce irritation of the respiratory system, in a significant number of individuals, following inhalation. In contrast to most organs, the lung is able to respond to a chemical insult by first removing or neutralising the irritant and then repairing the damage. The repair process, which initially evolved to protect mammalian lungs from foreign matter and antigens, may however, produce further lung damage resulting in the impairment of gas exchange, the primary function of the lungs.

Respiratory tract irritation often results in an inflammatory response involving the recruitment and activation of many cell types, mainly derived from the vascular system.

Acute effects from inhalation of high concentrations of vapour are pulmonary irritation, including coughing, with nausea; central nervous system depression - characterised by headache and dizziness, increased reaction time, fatigue and loss of co-ordination.

The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing.

Before starting consider control of exposure by mechanical ventilation.

CHRONIC HEALTH EFFECTS

» On the basis, primarily, of animal experiments, concern has been expressed that the material may produce carcinogenic or mutagenic effects; in respect of the available information, however, there presently exists

continued...

EVIC 853-859A SPRAYTHANE TEXTURED POLYURETHANE PART A

Chemwatch Material Safety Data Sheet

Issue Date: 26-Sep-2008

NA317TC

CHEMWATCH 5093-30

Version No:4

CD 2008/4 Page 13 of 19

Section 11 - TOXICOLOGICAL INFORMATION

inadequate data for making a satisfactory assessment.

There is sufficient evidence to provide a strong presumption that human exposure to the material may result in impaired fertility on the basis of: - clear evidence in animal studies of impaired fertility in the absence of toxic effects, or evidence of impaired fertility occurring at around the same dose levels as other toxic effects but which is not a secondary non-specific consequence of other toxic effects.

There is sufficient evidence to provide a strong presumption that human exposure to the material may result in developmental toxicity, generally on the basis of:

- clear results in appropriate animal studies where effects have been observed in the absence of marked maternal toxicity, or at around the same dose levels as other toxic effects but which are not secondary non-specific consequences of the other toxic effects.

Limited evidence suggests that repeated or long-term occupational exposure may involve organs or biochemical systems.

produce cumulative

TOXICITY AND IRRITATION

» unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

» The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.

For ethylene glycol:

Ethylene glycol is quickly and extensively absorbed through the gastrointestinal tract. Limited information suggests that it is also absorbed through the respiratory tract; dermal absorption is apparently slow.

Following absorption, ethylene glycol is distributed throughout the body according to total body water. In most mammalian species, including humans, ethylene glycol is initially metabolised by alcohol dehydrogenase to form glycolaldehyde, which is rapidly converted to glycolic acid and glyoxal by aldehyde oxidase and aldehyde dehydrogenase. These metabolites are oxidised to glyoxylate; glyoxylate may be further metabolised to formic acid, oxalic acid, and glycine. Breakdown of both glycine and formic acid can generate CO₂, which is one of the major elimination products of ethylene glycol. In addition to exhaled CO₂, ethylene glycol is eliminated in the urine as both the parent compound and glycolic acid. Elimination of ethylene glycol from the plasma in both humans and laboratory animals is rapid after oral exposure; elimination half-lives are in the range of 1-4 hours in most species tested.

Respiratory Effects. Respiratory system involvement occurs 12-24 hours after ingestion of sufficient amounts of ethylene glycol and is considered to be part of a second stage in ethylene glycol poisoning symptoms include hyperventilation, shallow rapid breathing, and generalized pulmonary edema with calcium oxalate crystals occasionally present in the lung parenchyma. Respiratory system involvement appears to be dose-dependent and occurs concomitantly with cardiovascular changes. Pulmonary infiltrates and other changes compatible with adult respiratory distress syndrome (ARDS) may characterise the second stage of ethylene glycol poisoning. Pulmonary oedema can be secondary to cardiac failure, ARDS, or aspiration of gastric contents. Symptoms related to acidosis such as hyperpnea and tachypnea are frequently observed; however, major respiratory morbidities such as pulmonary edema and bronchopneumonia are relatively rare and usually only observed with extreme poisoning (e.g., in only 5 of 36 severely poisoned cases).

Cardiovascular Effects. Cardiovascular system involvement in humans occurs at the same time as respiratory system involvement, during the second phase of oral ethylene glycol poisoning, which is 12- 24 hours after acute exposure. The symptoms of cardiac involvement include tachycardia, ventricular gallop enlargement. Ingestion of ethylene glycol may also cause hypertension or hypotension, which may progress to cardiogenic shock. Myocarditis has been observed at autopsy in cases of people who died following acute ingestion of ethylene glycol. As in the case of respiratory effects, cardiovascular involvement occurs with ingestion of relatively high doses of ethylene glycol.

Nevertheless, circulatory disturbances are a rare occurrence, having been reported in only 8 of 36 severely poisoned cases. Therefore, it appears that acute exposure to high levels of ethylene glycol can cause serious cardiovascular effects in humans. The effects of a long-term, low-dose exposure are unknown.

Gastrointestinal Effects. Nausea, vomiting with or without blood, pyrosis, and abdominal cramping and pain are common early effects of acute ethylene glycol ingestion. Acute effects of ethylene glycol ingestion in one patient included intermittent diarrhea and abdominal pain, which were attributed to mild colonic ischaemia; severe abdominal pain secondary to colonic stricture and perforation developed 3 months after ingestion, and histology of the resected colon showed birefringent crystals highly suggestive of oxalate deposition.

Musculoskeletal Effects. Reported musculoskeletal effects in cases of acute ethylene glycol poisoning have

continued...

EVIC 853-859A SPRAYTHANE TEXTURED POLYURETHANE PART A

Chemwatch Material Safety Data Sheet

Issue Date: 26-Sep-2008

NA317TC

CHEMWATCH 5093-30

Version No:4

CD 2008/4 Page 14 of 19

Section 11 - TOXICOLOGICAL INFORMATION

included diffuse muscle tenderness and myalgias associated with elevated serum creatinine phosphokinase levels, and myoclonic jerks and tetanic contractions associated with hypocalcaemia.

Hepatic Effects. Central hydropic or fatty degeneration, parenchymal necrosis, and calcium oxalate crystals in the liver have been observed at autopsy in cases of people who died following acute ingestion of ethylene glycol.

Renal Effects. Adverse renal effects after ethylene glycol ingestion in humans can be observed during the third stage of ethylene glycol toxicity 24-72 hours after acute exposure. The hallmark of renal toxicity is the presence of birefringent calcium oxalate monohydrate crystals deposited in renal tubules and their presence in urine after ingestion of relatively high amounts of ethylene glycol. Other signs of nephrotoxicity can include tubular cell degeneration and necrosis and tubular interstitial inflammation. If untreated, the degree of renal damage caused by high doses of ethylene glycol progresses and leads to haematuria, proteinuria, decreased renal function, oliguria, anuria, and ultimately renal failure. These changes in the kidney are linked to acute tubular necrosis but normal or near normal renal function can return with adequate supportive therapy.

Metabolic Effects. One of the major adverse effects following acute oral exposure of humans to ethylene glycol involves metabolic changes. These changes occur as early as 12 hours after ethylene glycol exposure. Ethylene glycol intoxication is accompanied by metabolic acidosis which is manifested by decreased pH and bicarbonate content of serum and other bodily fluids caused by accumulation of excess glycolic acid. Other characteristic metabolic effects of ethylene glycol poisoning are increased serum anion gap, increased osmolal gap, and hypocalcaemia. Serum anion gap is calculated from concentrations of sodium, chloride, and bicarbonate, is normally 12-16 mM, and is typically elevated after ethylene glycol ingestion due to increases in unmeasured metabolite anions (mainly glycolate).

Neurological Effects: Adverse neurological reactions are among the first symptoms to appear in humans after ethylene glycol ingestion. These early neurotoxic effects are also the only symptoms attributed to unmetabolised ethylene glycol. Together with metabolic changes, they occur during the period of 30 minutes to 12 hours after exposure and are considered to be part of the first stage in ethylene glycol intoxication. In cases of acute intoxication, in which a large amount of ethylene glycol is ingested over a very short time period, there is a progression of neurological manifestations which, if not treated, may lead to generalized seizures and coma. Ataxia, slurred speech, confusion, and somnolence are common during the initial phase of ethylene glycol intoxication as are irritation, restlessness, and disorientation.

Cerebral edema and crystalline deposits of calcium oxalate in the walls of small blood vessels in the brain were found at autopsy in people who died after acute ethylene glycol ingestion.

Effects on cranial nerves appear late (generally 5-20 days post-ingestion), are relatively rare, and according to some investigators constitute a fourth, late cerebral phase in ethylene glycol intoxication.

Clinical manifestations of the cranial neuropathy commonly involve lower motor neurons of the facial and bulbar nerves and are reversible over many months.

Reproductive Effects: Reproductive function after intermediate-duration oral exposure to ethylene glycol has been tested in three multi-generation studies (one in rats and two in mice) and several shorter studies (15-20 days in rats and mice). In these studies, effects on fertility, foetal viability, and male reproductive organs were observed in mice, while the only effect in rats was an increase in gestational duration.

Developmental Effects: The developmental toxicity of ethylene glycol has been assessed in several acute-duration studies using mice, rats, and rabbits. Available studies indicate that malformations, especially skeletal malformations occur in both mice and rats exposed during gestation; mice are apparently more sensitive to the developmental effects of ethylene glycol. Other evidence of embryotoxicity in laboratory animals exposed to ethylene glycol exposure includes reduction in foetal body weight.

Cancer: No studies were located regarding cancer effects in humans or animals after dermal exposure to ethylene glycol.

Genotoxic Effects: Studies in humans have not addressed the genotoxic effects of ethylene glycol. However, available in vivo and in vitro laboratory studies provide consistently negative genotoxicity results for ethylene glycol.

2-ETHOXYETHYL ACETATE:

» unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (rat) LD50: 2900 mg/kg

Inhalation (rat) LC50: 12100 mg/m³/8 h Dermal (rabbit):420

mg(open)- Mild

IRRITATION

Eye (rabbit): 40 mg - Moderate

continued...

EVIC 853-859A SPRAYTHANE TEXTURED POLYURETHANE PART A

Chemwatch Material Safety Data Sheet

Issue Date: 26-Sep-2008

NA317TC

CHEMWATCH 5093-30

Version No:4

CD 2008/4 Page 15 of 19

Section 11 - TOXICOLOGICAL INFORMATION

Dermal (rabbit) LD50: 10500 mg/kg

Inhalation (rat) TCLo: 50 ppm/6 h

» The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.

Exposure to the material for prolonged periods may cause physical defects in the developing embryo (teratogenesis).

TOLUENE:

» unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (human) LDLo: 50 mg/kg

Oral (rat) LD50: 636 mg/kg

Inhalation (human) TCLo: 100 ppm

Inhalation (man) TCLo: 200 ppm

Inhalation (rat) LC50: >26700 ppm/1h

Dermal (rabbit) LD50: 12124 mg/kg

» The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.

For toluene:

Acute Toxicity

Humans exposed to intermediate to high levels of toluene for short periods of time experience adverse central nervous system effects ranging from headaches to intoxication, convulsions, narcosis, and death. Similar effects are observed in short-term animal studies.

Humans - Toluene ingestion or inhalation can result in severe central nervous system depression, and in large doses, can act as a narcotic. The ingestion of about 60 mL resulted in fatal nervous system depression within 30 minutes in one reported case.

Constriction and necrosis of myocardial fibers, markedly swollen liver, congestion and haemorrhage of the lungs and acute tubular necrosis were found on autopsy.

Central nervous system effects (headaches, dizziness, intoxication) and eye irritation occurred following inhalation exposure to 100 ppm toluene 6 hours/day for 4 days.

Exposure to 600 ppm for 8 hours resulted in the same and more serious symptoms including euphoria, dilated pupils, convulsions, and nausea. Exposure to 10,000-30,000 ppm has been reported to cause narcosis and death

Toluene can also strip the skin of lipids causing dermatitis

Animals - The initial effects are instability and incoordination, lachrymation and snuffles (respiratory exposure), followed by narcosis. Animals die of respiratory failure from severe nervous system depression.

Cloudy swelling of the kidneys was reported in rats following inhalation exposure to 1600 ppm, 18-20 hours/day for 3 days

Subchronic/Chronic Effects:

Repeat doses of toluene cause adverse central nervous system effects and can damage the upper respiratory system, the liver, and the kidney. Adverse effects occur as a result from both oral and the inhalation exposures. A reported lowest-observed-effect level in humans for adverse neurobehavioral effects is 88 ppm.

Humans - Chronic occupational exposure and incidences of toluene abuse have resulted in hepatomegaly and liver function changes. It has also resulted in nephrotoxicity and, in one case, was a cardiac sensitiser and fatal cardiotoxin.

Neural and cerebellar dystrophy were reported in several cases of habitual "glue sniffing." An epidemiological study in France on workers chronically exposed to toluene fumes reported leukopenia and neutropenia. Exposure levels were not given in the secondary reference; however, the average urinary excretion of hippuric acid, a metabolite of toluene, was given as 4 g/L compared to a normal level of 0.6 g/L

Animals - The major target organs for the subchronic/chronic toxicity of toluene are the nervous system, liver, and kidney. Depressed immune response has been reported in male mice given doses of 105 mg/kg/day for 28 days. Toluene in corn oil administered to F344 male and female rats by gavage 5 days/week for 13 weeks, induced prostration, hypoactivity, ataxia, piloerection, lachrymation, excess salivation, and body

continued...

EVIC 853-859A SPRAYTHANE TEXTURED POLYURETHANE PART A

Chemwatch Material Safety Data Sheet

Issue Date: 26-Sep-2008

NA317TC

CHEMWATCH 5093-30

Version No:4

CD 2008/4 Page 16 of 19

Section 11 - TOXICOLOGICAL INFORMATION

tremors at doses 2500 mg/kg. Liver, kidney, and heart weights were also increased at this dose and histopathologic lesions were seen in the liver, kidneys, brain and urinary bladder. The no-observed-adverse effect level (NOAEL) for the study was 312 mg/kg (223 mg/kg/day) and the lowest-observed-adverse effect level (LOAEL) for the study was 625 mg/kg (446 mg/kg/day) .

Developmental/Reproductive Toxicity

Exposures to high levels of toluene can result in adverse effects in the developing human foetus. Several studies have indicated that high levels of toluene can also adversely effect the developing offspring in laboratory animals.

Humans - Variable growth, microcephaly, CNS dysfunction, attentional deficits, minor craniofacial and limb abnormalities, and developmental delay were seen in three children exposed to toluene in utero as a result of maternal solvent abuse before and during pregnancy

Animals - Sternebral alterations, extra ribs, and missing tails were reported following treatment of rats with 1500 mg/m³ toluene 24 hours/day during days 9-14 of gestation. Two of the dams died during the exposure. Another group of rats received 1000 mg/m³ 8 hours/day during days 1-21 of gestation. No maternal deaths or toxicity occurred, however, minor skeletal retardation was present in the exposed fetuses. CFLP

Mice were exposed to 500 or 1500 mg/m³ toluene continuously during days 6-13 of pregnancy. All dams died at the high dose during the first 24 hours of exposure, however none died at 500 mg/m³. Decreased foetal weight was reported, but there were no differences in the incidences of skeletal malformations or anomalies between the treated and control offspring.

Absorption - Studies in humans and animals have demonstrated that toluene is readily absorbed via the lungs and the gastrointestinal tract. Absorption through the skin is estimated at about 1% of that absorbed by the lungs when exposed to toluene vapor.

Dermal absorption is expected to be higher upon exposure to the liquid; however, exposure is limited by the rapid evaporation of toluene .

Distribution - In studies with mice exposed to radiolabeled toluene by inhalation, high levels of radioactivity were present in body fat, bone marrow, spinal nerves, spinal cord, and brain white matter. Lower levels of radioactivity were present in blood, kidney, and liver. Accumulation of toluene has generally been found in adipose tissue, other tissues with high fat content, and in highly vascularised tissues .

Metabolism - The metabolites of inhaled or ingested toluene include benzyl alcohol resulting from the hydroxylation of the methyl group. Further oxidation results in the formation of benzaldehyde and benzoic acid. The latter is conjugated with glycine to yield hippuric acid or reacted with glucuronic acid to form benzoyl glucuronide. o-cresol and p-cresol formed by ring hydroxylation are considered minor metabolites

Excretion - Toluene is primarily (60-70%) excreted through the urine as hippuric acid. The excretion of benzoyl glucuronide accounts for 10-20%, and excretion of unchanged toluene through the lungs also accounts for 10-20%. Excretion of hippuric acid is usually complete within 24 hours after exposure.

CARCINOGEN

toluene	International Agency for Research on Cancer (IARC) Carcinogens	Group	3
---------	--	-------	---

REPROTOXIN

toluene	ILO Chemicals in the electronics industry that have toxic effects on reproduction	Reduced fertility or sterility
---------	---	--------------------------------

SKIN

2- ethoxyethyl acetate	Australia Exposure Standards - Skin	Notes	Sk
toluene	Australia Exposure Standards - Skin	Notes	Sk

continued...

EVIC 853-859A SPRAYTHANE TEXTURED POLYURETHANE PART A

Chemwatch Material Safety Data Sheet

Issue Date: 26-Sep-2008

NA317TC

CHEMWATCH 5093-30

Version No:4

CD 2008/4 Page 17 of 19

Section 12 - ECOLOGICAL INFORMATION

This material and its container must be disposed of as hazardous waste.

Section 13 - DISPOSAL CONSIDERATIONS

- Containers may still present a chemical hazard/ danger when empty.
- Return to supplier for reuse/ recycling if possible.

Otherwise:

- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.

- Where possible retain label warnings and MSDS and observe all notices pertaining to the product.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction,
- Reuse
- Recycling
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

- DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Dispose of by: Burial in a licenced land-fill or Incineration in a licenced apparatus (after admixture with suitable combustible material).
- Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

Section 14 - TRANSPORTATION INFORMATION

Labels Required: FLAMMABLE LIQUID

HAZCHEM: 3[Y]E (ADG6)

UNDG:

Dangerous Goods Class:	3	Subrisk:	None
UN Number:	1263	Packing Group:	II
Shipping Name: PAINT RELATED MATERIAL (including paint thinning or reducing compound)			

Air Transport IATA:

ICAO/IATA Class:	3	ICAO/IATA Subrisk:	None
UN/ID Number:	1263	Packing Group:	II
Special provisions:	A3 A72		
Shipping name: PAINT RELATED MATERIAL			

Maritime Transport IMDG:

IMDG Class:	3	IMDG Subrisk:	None
UN Number:	1263	Packing Group:	II
EMS Number:	F- E, S- E	Special provisions:	163 944
Limited Quantities:	5 L	Marine Pollutant:	Not Determined

continued...

EVIC 853-859A SPRAYTHANE TEXTURED POLYURETHANE PART A

Chemwatch Material Safety Data Sheet

Issue Date: 26-Sep-2008

NA317TC

CHEMWATCH 5093-30

Version No:4

CD 2008/4 Page 18 of 19

Section 14 - TRANSPORTATION INFORMATION

Shipping Name: PAINT (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE: S5

REGULATIONS

Evic 853-859A Spraythane Textured Polyurethane Part A (CAS: None):

No regulations applicable

2-ethoxyethyl acetate (CAS: 111-15-9) is found on the following regulatory lists;

- Australia Exposure Standards
- Australia Hazardous Substances
- Australia Inventory of Chemical Substances (AICS)
- Australia National Pollutant Inventory
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Appendix E (Part 2)
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Appendix F (Part 3)
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Appendix I
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Schedule 6
- GESAMP/EHS Composite List of Hazard Profiles - Hazard evaluation of substances transported by ships
- IMO IBC Code Chapter 17: Summary of minimum requirements
- IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk
- OECD Representative List of High Production Volume (HPV) Chemicals

toluene (CAS: 108-88-3) is found on the following regulatory lists;

- Australia - Australian Capital Territory - Environment Protection Regulation: Ambient environmental standards (Domestic water supply - organic compounds)
- Australia - Australian Capital Territory - Environment Protection Regulation: Pollutants entering waterways taken to cause environmental harm (Aquatic habitat)
- Australia - Australian Capital Territory Environment Protection Regulation Ecosystem maintenance - Organic chemicals - Non-pesticide anthropogenic organics
- Australia - Australian Capital Territory Environment Protection Regulation Pollutants entering waterways - Domestic water quality
- Australia Exposure Standards
- Australia Hazardous Substances
- Australia High Volume Industrial Chemical List (HVICL)
- Australia Illicit Drug Reagents/Essential Chemicals - Category III
- Australia Inventory of Chemical Substances (AICS)
- Australia National Pollutant Inventory
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Appendix E (Part 2)
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Appendix F (Part 3)
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Appendix I
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Schedule 5
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Schedule 6
- GESAMP/EHS Composite List of Hazard Profiles - Hazard evaluation of substances transported by ships
- IMO IBC Code Chapter 17: Summary of minimum requirements
- IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk
- IMO Provisional Categorization of Liquid Substances - List 1: Pure or technically pure products
- International Agency for Research on Cancer (IARC) Carcinogens
- OECD Representative List of High Production Volume (HPV) Chemicals
- United Nations Convention Against Illicit Traffic in Narcotic Drugs and Psychotropic Substances - Table II
- United Nations List of Precursors and Chemicals Frequently used in the Illicit Manufacture of Narcotic Drugs and Psychotropic Substances Under International Control - Table II
- WHO Guidelines for Drinking-water Quality - Guideline values for chemicals that are of health significance in drinking-water

Section 16 - OTHER INFORMATION

REPRODUCTIVE HEALTH GUIDELINES

» Established occupational exposure limits frequently do not take into consideration reproductive end points that are clearly below the thresholds for other toxic effects. Occupational reproductive guidelines (ORGs) have been suggested as an additional standard. These have been established after a literature search for reproductive no-observed-adverse effect-level (NOAEL) and the lowest-observed-adverse-effect-level (LOAEL). In addition the US EPA's procedures for risk assessment for hazard identification and dose-response assessment as applied by NIOSH were used in the creation of such limits. Uncertainty factors (UFs) have also been incorporated.

continued...

EVIC 853-859A SPRAYTHANE TEXTURED POLYURETHANE PART A

Chemwatch Material Safety Data Sheet

Issue Date: 26-Sep-2008

NA317TC

CHEMWATCH 5093-30

Version No:4

CD 2008/4 Page 19 of 19

Section 16 - OTHER INFORMATION

Ingredient	ORG	UF	Endpoint	CR	Adeq TLV
toluene	9.6 mg/m3	10	D	NA	-

» These exposure guidelines have been derived from a screening level of risk assessment and should not be construed as unequivocally safe limits. ORGS represent an 8-hour time-weighted average unless specified otherwise.

CR = Cancer Risk/10000; UF = Uncertainty factor:

TLV believed to be adequate to protect reproductive health:

LOD: Limit of detection

Toxic endpoints have also been identified as:

D = Developmental; R = Reproductive; TC = Transplacental carcinogen

Jankovic J., Drake F.: A Screening Method for Occupational Reproductive

American Industrial Hygiene Association Journal 57: 641-649 (1996).

» Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references.

» The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 26-Sep-2008

Print Date: 3-Dec-2008